

# **UV Roll to Roll Printer**

## **UR-2000S**


#### • Features 特点



#### Precisioncore Technology

Machine is equipped with Epson i3200-U printhead, powered by advanced precisioncore technology, born for speed and resolution.

爱普生i3200-U 喷头,采用Precisioncore技术,为速 度而生



#### Material Tension System

Tension media feeding system is standard equipped to guarantee the high accuracy of material stepping.

张力放布系统。保障高精度步进。



#### **Negative Pressure System**

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨,简化多头设备维护。



#### Dual guide rail

Dual guide rail configuration, guarantee the stability of long time running.

双导轨设计,提高设备长时间运行的稳定性



#### Anti-collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

小车遇撞击自动停止,并支持中断处续打,减少意外带 来的材料浪费

\* Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.

精心设计的张力收放布系统,精确走步

- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation. 成熟的白墨定时搅拌装置,有效防止UV白墨沉淀
- ★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company. 简约大气的外观设计



### ● Specification 参数

Model No.		型号	UR-2000S
Printing Head		打印喷头	4 × Epson i3200-U
Resolution		打印精度	2400 dpi MAX
Media 耗材	Width	耗材宽度	2000 mm MAX
	Туре	耗材种类	Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、服装、皮革、PET膜、反光膜以及其他众多卷材
Ink 墨水	Туре	墨水类型	UV Ink
	Color	墨水颜色	CMYK/CMYK+W / CMYK+W+V
	Curing	墨水固化	High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯
Speed 速度	Color Mode 颜色模式		СМҮК
	Draft	草图模式	108 m²/h
	Production 标准模式		80 m²/h
	Quality	精细模式	54 m²/h
Ink Supply System 供墨系统		供墨系统	Two advanced separate negative pressure systems (One for color and varnish, One for white).
Cleaning		清洗系统	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头
Feed & TakeUp		收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布
Rip Software		操作软件	Photoprint
Connector		连接方式	USB 3.0
Power		电力消耗	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX
Size 尺寸	Machine	机器尺寸	L3770 x W920 x H1710 mm
	Packing	包装尺寸	L3870 x W1020 x H1940 mm
Weight 重量	Machine	机器重量	850 KG
	Packing	机器重量	1100 KG
	a ara aubiaat ta	ahanga without n	otice 以上参数可能随机器版本改变,清以厂家最新数据为准。 SinoCole